

using H-SPICE tools. From simulation result we can adjust trans-conductance from 2uS to 222uS by driving external bias voltage from 1.0V to 1.9V. Our OTA circuit can be used for active filter of CDMA also other device that use other frequency bands.

References

1. Hollman, T., Lindfors, S., Lansirinne, M., Jussila J., Halonen, K. A. I.: A 2.7V CMOS dual-mode baseband filter for PDC and WCDMA, IEEE Journal of Solid-state Circuits, Vol. 36, pp. 1148-1153, July (2001).
2. Bang, J.-H.: The Design of A CMOS Gm-C Lowpass Filter with Variable
3. Lee, W., Bang, J.: A Multi-channel CMOS Low-voltage Filter with Newly Current-mode Integrator.
4. Kim, S. H.: Folded-Cascode Operational Amplifier for 32X32 IRFPA Readout Integrated Circuit using the 0.35 μ m CMOS process. School of Nano engineering, Inje University
5. Razavi, B.: Design of Analog CMOS Integrated Circuit. pp 122-125, pp 139-146
6. Choi, H.-J., Choi, J.-K., Kim, H.-S.: A Design of Low Frequency Noise Figure Improvement of RF Circuit for Direct Conversion Receiver. ITFE J. of Summer Conference, Vol. 2009, pp. 305-308, August. (2009).
7. Bang, J.-H.: "The Design of A CMOS GM-C Lowpass Filter with Variable Cutoff Frequency for Direct Conversion Receiver" The Transactions of the Korean Institute of Electrical Engineers. Vol.57, pp.1464-1469, Aug (2008).
8. Lim, S.H.: A channel-selection switched capacitor filter. Proc. IEEE 47th Midwest Symp. Circuits and Systems, pp. I-117-I-120, Hiroshima, Japan, July (2004).
9. Jeong, T., Bang, J.: CMOS Low-voltage Filter For RFID Reader Using A Self-biased Transconductor. KAIS. Vol.10, pp. 1526-1531, July. (2009).
10. Wittlinger, H.A.: Applications of the CA3080 and CA3080A High Performance Operational Transconductance Amplifiers. RCA Application Note ICAN-6668.