

part according to frequency, it has quite stable dielectric constant in the condition of drive within 1MHz.

References

1. U. Kogelschatz, IEEE Trans. Plasma Sci., 30 (2002) 1400.
2. K. Takaki, K. Urashima, and J-S. Chang, IEEE Trans. Plasma Sci. 32 (2004) 2175.
3. O. Goossens, E. Dekempeneer, D. Vangeneugden, R. Van de Leest and C. Leys, Surf. Coat. Technol. 142-144 (2001) 474
4. G. Borcia, C. A. Anderson and N. M. D. Brown, Appl. Surf. Sci. 225 (2004) 186.
5. U. Konelschatz, B. Eliasson and W. Egli, J. PHYS IV FRANCE 7 (1 997)
6. Seung Bo Shim a, Sung-Yong Cho a, Don Kyu Lee b, In Cheol Song a, Chung Hoo Park a, Ho-Jun Lee a, Hae June Lee, Thin Solid Films 518 (2010) 3037–3041
7. Shin Young Kyo, Shon Chae Hwa, Kim Woong, Lee Jae Koo, IEEE Trans. Plasma Sci. 27 (1999) 1366.
8. Lee Hae June, Kim Hyun Chul, Yang Sung Soo, Lee Jae Koo, Phys. Plasmas 9 (2002) 2822.
9. S.S. Yang, S.M. Lee, F. Iza, J.K. Lee, J. Phys. D: Appl Phys. 39 (2006) 2775.
10. H.C. Kim, M.S. Hur, S.S. Yang, S.W. Shin, J.K. Lee, J. Appl. Phys. 91 (2002) 9513.
11. Chung-Hoo Park, “Plasma Display”, PNU, 2001